

CENTRIFUGES

FULL SWING-OUT ROTOR

M 4815P

Capacity/Standard rotor	48 x 15 ml
Optional rotors	20x10 / 4 x 50 / 4 x 100 ml
Max. speed	4500 rpm
Max. RCF	3622 x g
Speed setting increment	10 rpm
Speed setting range	500 - 4500 rpm
Acceleration & deceleration time	20-150 seconds in step of 1 sec
Timer	Starts when set speed achieved
Timer range	1-99 min. In 1 minute step
Continuous running mode	Available
Running by entering RCF value	Available
Working short periods	With pulse button
Number of programs	10
Fuse	6 Amps
Power rating	350 W
Safety measure	Lid safety switch
Lid lock	Available
External speed reading	Available
Rotor material	Aluminum
Tube socket (godet) material	Acetal resin
Casing material	Sheet steel finished in stoved enamel paint + ABS
Chamber material	Stainless steel
Motor type	Maintenance free, brushless motor
Power supply	AC 190-240 V / 50-60 Hz
Overall dimensions (w x h x d)	44 x 38 x 54 cm
Net weight	27 kg
Gross weight	30 kg

4.3" TFT Touch Screen Display

Speed RCF and time control, acceleration / deceleration time



16 x 15 ml 28 x 15 ml 48 x 15 ml 20 x 10 ml 4 x 50 ml 4 x 100 ml