

# CENTRIFUGES

## MICROHAEMATOCRIT CENTRIFUGE

### M 19P II

<b>Capacity (Capillary tubes)</b>	24 pcs x (Ø2 x 75 mm)
<b>Timer</b>	Starts when set speed achieved
<b>Timer range</b>	1-99 minutes In 1 minute step
<b>Max. speed</b>	12000 rpm
<b>Max. RCF</b>	14489 x g
<b>Running by entering RCF value</b>	Available
<b>Speed setting increment</b>	10 rpm
<b>Speed setting range</b>	1000 - 12000 rpm
<b>Acceleration &amp; deceleration time</b>	20-150 seconds in step of 1 sec
<b>Safety measure</b>	Lid safety switch
<b>Lid lock</b>	Available
<b>External speed reading</b>	Available
<b>Working short periods</b>	With pulse button
<b>Number of programs</b>	10
<b>Fuse</b>	3 Amps
<b>Motor type</b>	Maintenance free, brushless motor
<b>Power rating</b>	350 W
<b>Reading scale capacity</b>	0-100 %
<b>Reading scale measurement limits</b>	45-70 mm
<b>Tube holding disc material</b>	Aluminum
<b>Tube holding disc cover material</b>	Stainless steel
<b>Casing material</b>	Sheet steel finished in stoved enamel paint + ABS
<b>Chamber material</b>	Stainless steel
<b>Power source</b>	AC 190-240 V / 50-60 Hz
<b>Overall dimensions (w x h x d)</b>	33 x 30 x 45 cm
<b>Net weight</b>	16 kg
<b>Gross weight</b>	18 kg

### 4.3" TFT Touch Screen Display

Speed RCF and time control, acceleration / deceleration time



24 pcs x (Ø2 x 75 mm)