

# CENTRIFUGES

## FIXED ANGLE ROTOR

Digital

### M 4812P II

<b>Capacity</b>	12 x 15 ml
<b>Rotor type</b>	Vertical 35° fixed angle
<b>Max. speed</b>	5000 rpm
<b>Max. RCF</b>	3057 x g
<b>Speed setting increment</b>	10 rpm
<b>Speed setting range</b>	500 - 5000 rpm
<b>Timer</b>	Starts when set speed achieved
<b>Timer range</b>	1-99 min. In 1 minute step
<b>Continuous running mode</b>	Available
<b>Running by entering RCF value</b>	Available
<b>Working short periods</b>	With pulse button
<b>Number of programs</b>	10
<b>Fuse</b>	6 Amps
<b>Power rating</b>	350 W
<b>Safety measure</b>	Lid safety switch
<b>Lid lock</b>	Available
<b>External speed reading</b>	Available
<b>Rotor material</b>	Polycarbonate
<b>Tube socket (godet) material</b>	ABS (rigid plastic)
<b>Casing material</b>	Sheet steel finished in stoved enamel paint + ABS
<b>Motor type</b>	Maintenance free, brushless motor
<b>Power supply</b>	AC 190-240 V / 50-60 Hz
<b>Overall dimensions (w x h x d)</b>	33 x 30 x 45 cm
<b>Net weight</b>	16 kg
<b>Gross weight</b>	18 kg

### 4.3" TFT Touch Screen Display

Speed RCF and time control, acceleration / deceleration time

