

# STERILIZERS

## HOT AIR STERILIZERS

With Aluminum Chamber

### M 3025 P

**Working temperature range**

Ambient temperature +5 °C to 250 °C

**Capacity (Chamber volume)**

24 lt

**Type of thermoelement**

J type

**Temperature control**

PID Digital control

**Load switching element**

SSR (Solid State Relay)

**Thermostat setting increments**

in 1 °C steps

**Thermostat working accuracy**

± 1 °C

**Thermometer display increments**

in 1 °C steps

**Chamber temperature accuracy**

± 2 °C

**Postpone / Process time**

1 min – 99 hours 59 min

**Timing begins**

When reached set temperature value

**Safety measure**

Safety thermostat with liquid expansion (50-300) °C

**Casing material**

Sheet steel finished in stoved enamel paint

**Chamber material**

Anodized aluminum

**Insulation material**

Rock wool

**Shelf**

2 Perforated anodized aluminum

**Fuse**

6 Amps

**Power rating**

650 W

**Power supply**

AC 190-240 V / 50-60 Hz

**Chamber dimensions (w x h x d)**

29 x 31 x 27 cm

**Overall dimensions (w x h x d)**

58 x 50 x 41 cm

**Net weight**

23 kg

**Gross weight**

27 kg

