

# INCUBATORS

## COOLED INCUBATOR

With Stainless Steel Chamber

### M 7040R

<b>Working temperature range</b>	-10 °C to 80 °C
<b>Capacity (Chamber volume)</b>	125 lt.
<b>Type of thermoelement</b>	Pt - 100
<b>Temperature control</b>	PID Digital control
<b>Load switching element</b>	SSR (Solid State Relay)
<b>Thermostat setting increments</b>	in 0.1 °C steps
<b>Thermostat working accuracy</b>	± 0.1 °C
<b>Thermometer display increments</b>	in 0.1 °C steps
<b>Chamber temperature accuracy</b>	± 1 °C
<b>Gas type</b>	R134a
<b>Circulating fan</b>	Available
<b>Observation window</b>	Available
<b>Chamber dome light</b>	Available
<b>Safety measure</b>	Safety thermostat with liquid expansion (30-90) °C
<b>Casing material</b>	Sheet steel finished in stoved enamel paint
<b>Chamber material</b>	Stainless steel
<b>Insulation material</b>	Rock wool
<b>Shelf</b>	2 PVC coated wire
<b>Fuse</b>	16 Amps.
<b>Power rating</b>	950 W
<b>Power supply</b>	AC 190-240 V / 50-60 Hz
<b>Chamber dimensions (w x h x d)</b>	50 x 50 x 50 cm.
<b>Overall dimensions (w x h x d)</b>	65 x 95 x 75 cm.
<b>Net weight</b>	83 kg.
<b>Gross weight</b>	100 kg.

